

# User Information Sheet



## Description

Foul Weather High Visibility Warning Trousers, CLASS 1 area of fluorescent YELLOW or ORANGE coated background and retro reflective tape. Two horizontal bands around leg of LEVEL 2 retro reflective tape. EN 343 Class 3 (highest) water penetration Class 1 (lowest) water vapour resistance.

This garment, when worn on highways, provides a clear signal of the wearer's presence whilst also alerting other road users to a possible hazard.

## Specification

EN ISO 20471:2013+A1:2016


EN 343:2003 +A1:2007

RIS/3279/TOM Issue 1:2016

This garment bears the CE marking to demonstrate compliance with EU 2016/ 425 and the UKCA marking to demonstrate compliance with UK Legislation UK2019 Schedule 35 Regulation 38



3  
1



1

## Numerals

- refers to the design classification. Rated between 1 & 3 with 3 giving the maximum amount of protection

## Storage/Transportation

Always store in clean, dry conditions. DO NOT store in places subject to direct strong sunlight. This garment is suitable for transportation as supplied by the manufacturer.

## Disposal

Dispose of garment according to local environmental guidelines.

## Limitations of Use

This garment is a conspicuity aid. Keep clean: Should the high visibility properties of this garment become unrecoverable, soiled or contaminated, replace the item with a new one.

To ensure optimum conspicuity this garment must be kept clean and regular comparisons are recommended against a new garment.

## After Care

For instructions on washing see care label in garment. Manufacturer will not accept liability for garments where care labels have been ignored, neglected, defaced or removed.

Do not wash in biological powder. Warm machine wash. Cold rinse. Short spin. Do not wring. Rinse well. Do not over dry.




The chromaticity and retro reflective properties have been tested after 5 washing cycles only.

## Available Sizes & Selection

Fit according to chest size. Allowance of approx 10-12"/25-30cm built in for comfort and to allow the garment to be worn over light layers of clothing. If bulkier clothing has to be worn underneath, a larger size may be required.

Size	Chest (cm)	Height (cms)
<b>Small</b>	86 - 94	164 - 172
<b>Medium</b>	94 - 102	172 - 180
<b>Large</b>	102 - 110	180 - 188
<b>X Large</b>	110 - 118	188 - 196
<b>2X Large</b>	118 - 129	196 - 204
<b>3X Large</b>	129 - 135	196 - 204
<b>4X Large</b>	135 - 147	196 - 204
<b>5X Large</b>	147 - 153	196 - 204
<b>6X Large</b>	153 - 159	196 - 204



## Recommendations for wearing time

Temperature of working environment °C	Class		
	1 R <sub>ef</sub> above 40	2 20 < R <sub>ef</sub> ≤ 40	3 R <sub>ef</sub> ≤ 20
25	60 Minutes	105 Minutes	205 Minutes
20	75 Minutes	250 Minutes	-
15	100 Minutes	-	-
10	240 Minutes	-	-
5	-	-	-

"-" means no limit for wearing time

## For further information please contact:

Rodo Limited  
Lumb Lane  
Droylsden  
Manchester  
M43 7BU  
United Kingdom  
Tel: 0161 371 6400  
Fax: 0161 371 6401

## Notified Body

INTERTEK ITALIA SpA – Via Miglioli,  
2/A Cernusco sul Naviglio (MI),  
Italy

Notified Body No. 2575

## Approved Body

ITS Testing Services UK Limited,  
Centre Court, Meridian Business Park  
Leicester  
LE19 1WD  
UK

Approved Body no. 0362