

TECHNICAL DATA SHEET

Product:	Black & Yellow Hazard Tape Self Adhesive
Variants:	48mm width
Product Codes:	BR4002000

Product Description.

It is made of soft polyvinyl chloride (PVC) film, coated with rubber pressure sensitive adhesive.

Also known as identification tape, tape, floor tape, landmark tape, etc.

Hazard tape has the advantages of the following properties waterproof, moisture-proof, weatherproof, anti-corrosion and anti-static, etc.

It is suitable for the anti-corrosion protection of airpipe waterpipes and other pipelines as well as ground signs and warnings.

Following data is provided for reference, users should assure themselves that the performance of the product is sufficient for their application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes.

Properties	Unit	Value	Test Method
Material Type	Polyvinyl chloride (PVC)		
Glue Type	Natural rubber		
Total Thickness	μ m	150	ASTM D 1000
Adhesion to Steel	N/25mm	3	ASTM D 1000
Initial Tack	#	10	GB/T 7125-2014
Tensile Strength	N/25mm	65	ASTM D 1000
Elongation	%	160	ASTM D 1000
Service Temperature	°C	0 to 60	
Applying Temperature	°C	10 to 40	

Storage:

1. Rolls should be stored, flat on their cut edges in their wrappings to avoid any pressure on the glued surface.
2. Rolls should be stored away from sources of heat for example direct sunlight and also frost, Ideal storage temperature is 23± 2°C, 50% relative humidity

Usage Tips:

The surface that the tape is to be applied to must be clean and free from dust and grease.

Others:

Tolerance: Thickness: $\pm 10\mu\text{m}$; Width: $\pm 1\text{mm}$; Length: CutRoll: $\pm 0.3\text{m}$

Remarks:

Individual rolls will vary slightly from above data, The user should determine whether the product
There is no Warranty of fitness for a particular purpose.