

WD-40 SPECIALIST® PTFE

DATA
SHEET



PRODUCT OVERVIEW

WD-40® Specialist® PTFE Lubricant contains PTFE which provides excellent lubrication and protection whilst reducing friction and wear, extending the life of tools and equipment. This product can be used on metals, glass, vinyl, rubber and plastic.



NARROW SPRAY



WIDE SPRAY

FEATURES & BENEFITS

- Dual action Smart Straw applicator for wide area and precision spray applications
- For the use of metals, glass, vinyl, rubber and plastic
- Extends life of tools and equipment
- Reduces friction and wear
- Long lasting formula provides superior lubrication
- Withstands temperatures of -20°C to +100°C

RECOMMENDED FOR:

Axels, Hydraulics, Hand & Power Tools, Cogs, Precision Tooling, Bushings, Conveyors, Sliding Tracks, Cranks, Wire Ropes and Pulleys.

DIRECTIONS FOR USE

Shake Well. Apply by spraying directly on surface to be lubricated or protected.

TECHNICAL DATA

Appearance	Cloudy, deep yellow liquid
Odour	Pleasant lemon smell
SG	0.75 - 0.78
Solubility	Not miscible with water
NSF Category	H2
Flammability	Classed as extremely flammable
Lubrication	Scar depth 0.38mm (ASTM D-4172)
Extreme Pressure	1000lb (ASTM 3233)

