

TECHNICAL DATA SHEET

Product:	Masking Tape
Variants:	48mm / 75mm widths
Product Codes:	BR4006001 / BR4006002

Following data is provided for reference, users should assure themselves that the performance of the product is sufficient for their application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes.

	Unit	Standard	Test Method
Total Thickness	μ m	120±10	GB/7125-1999
Ball Tack	#	≥5	GB/4852-2002
180° Peel Adhesion (to Stainless Steel)	N/in	≥6	GB/2792-1998
Tensile Strength	N/in	≥66	GB/7753-1987
Elongation	%	≥6	GB/T 30776-2014
Holding Power	H	≥2	GB/4851-2014

Storage:

1. Rolls should be stored, flat on their cut edges in their wrappings to avoid any pressure on the glued surface.
2. Rolls should be stored away from sources of heat for example direct sunlight and also frost, Ideal storage temperature is 25 ± 5°C

Usage Tips:

The surface that the tape is to be applied to must be clean and free from dust and grease.

Others:

This product meets RoHS requirements.

Remarks:

Individual rolls will vary slightly from above data, The user should determine whether the product is suitable for their particular applications.
There is no Warranty of fitness for a particular purpose.