

RILEY

STREAM EVO™


Stream Evo safety glasses provide extreme comfort and 'wearability' with a range of lens options to suit a variety of conditions.



TempFLEX™



SOFT TPE



ADJUSTABLE
NOSE BRIDGE



LIGHTWEIGHT



DIELECTRIC

KEY FEATURES

- + Single wraparound polycarbonate lens
- + Soft, ventilated TempFLEX™ temple tips provide a comfortable, secure fit
- + Slim temples enhance comfort when worn with ear defenders
- + Lateral protection
- + 100% metal free
- + Soft, adjustable, anti-slip nose bridge
- + Supplied with a microfibre storage pouch
- + Stream Evo Accessory Pack available separately. Contains adjustable headband & gasket
- + Also available in a smaller size - see Stream™ Evo Small
- + Also available without plastic packaging - see Stream™ (Evo) Eco

LENS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	○ RLY00361	2C-1.2 R 1FTKN CE / Z87+ U6 / IO 0	R EN 166 FT UK CE Z87+ / AS/NZS 1337.1 Lic. SMK40933	Impacts, UV radiations	TECTON 400 K&N Anti-scratch & Anti-fog / UV400 / Moisture repellent
GREY	● RLY00362	5-2.5 R 1FTKN CE / Z87+ U6 L2.5 / I 2		Impacts, UV & Solar radiations	

Other lens colours are available please contact your local branch of Lloyd & Jones

Available from
www.lloyd-jones.com



GENERAL SPECIFICATION

LENS BASE	9.5mm
WEIGHT	23g

PACKAGING

Individually contained in a polythene bag with a Euroslot

PER BOX	10
PER CARTON	200

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS	Polycarbonate	One piece moulded lens with side protection
NOSE BRIDGE	Thermoplastic Elastomers (TPE)	Comfortable and flexible
TEMPLE	TR90 Thermoplastic / Thermoplastic Elastomers (TPE)	Co-injected - Robust, flexible, lightweight and ventilated
HINGE	TR90 Thermoplastic	Metal free and durable


LENS & FRAME MARKINGS

LENS MARKINGS

LENS FILTER TYPE:
2, 2C UV | 4 IR fi lter | 5, 6 Solar fi lter | 1.7 to 7 Welding fi lter if no shade number

SCALE NUMBER (SHADE):

1.2 Clear or Amber 1.4 Blue or I/O Waterproof
1.7 Minimises or I/O 2.5 Grey or Revo 3.1 Dark Grey or Mirror

 Identity of manufacturer

OPTICAL CLASS:

1 High optical quality

MECHANICAL STRENGTH:

S Increased strength

F Low energy impact, resists a 6mm, 0.86g ball at 45m/s

B Medium energy impact, resists a 6mm, 0.86g ball at 120m/s

A High energy impact, resists a 6mm, 0.86g ball at 190m/s

T Protection against high-speed particles at extreme temperatures

PERFORMANCE:

8 Short circuit electric arc


9 Molten metal splash

K Resistance to scratches by fi ne particles

N Resistance to fogging

 Certifi cation mark

FRAME MARKINGS

 Identity of manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

MECHANICAL STRENGTH:

S Increased strength

F Low energy impact, resists a 6mm, 0.86 g ball at 45m/s

B Medium energy impact, resists a 6mm, 0.86 ball at 120m/s

A High energy impact, resists a 6mm, 0.86 ball at 190m/s

T Protection against high-speed particles at extreme temperatures

PERFORMANCE

3 Liquid droplets or splashes

4 Large dust particles > 5 µm

5 Gases and small dust particles < 5 µm

8 Short circuit electric arc

9 Molten metal and hot solids

 Certifi cation marks

USA (ANSI)

LENS:

U6 UV (All lenses) L1.3 LED L1.7 Solar (I/O, Twilight)

L2.5 Solar (Grey) L3 Solar (Dark Grey) W4 Infrared lens

LENS AND FRAME:

Z87+ High velocity impact, 0.25 inch, 1.04g ball at 150ft/s

AUS (AS/NZS)

LENS MARKINGS:

OCULAR CATEGORY:

0 UV 1 Solar 2 Solar

3 Solar O Outdoor untinted

MECHANICAL STRENGTH:

I Medium energy impact, resists a 6mm, 0.86g ball at 45m/s

FRAME MARKINGS:

AS/NZS 1337.1: 2010 guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

Riley product approval certifi cates to CE standards will be provided on request.

Riley is a registered trademark.

CERTIFICATION

Product conforms to the requirement of: UK Regulation 2016/425 on PPE, brought into UK Law and amended & Regulation (EU) 2016/425 of the European Parliament and of the Council as Personal Protective Equipment (PPE).

Type-Examination, (Module B), Certificates issued by: UK - SGS Limited., Rossmore Business Park, Ellesmere Port Cheshire CH65 3EN UK. [A.B. No.0120].
EU - SGS FIMKO OY., Takomotie 8, 00380 HELSINKI, Finland [N.B. No.0598]

Authorised Representative [EU]: Globus EMEA Ltd., 51 Dawson Street, Dublin, D02 AN25, Ireland.



Standard Mark
(SAI Global)

Available from:



www.lloyd-jones.com

E: sales@lloyd-jones.com

Manufactured by:

