

TECHNICAL DATA SHEET

Product:	Red/ White Barrier Tape
Variants:	70mm width
Product Codes:	BR4003000

Product Description.

Polyethylene heated extruded film, with aging resistance. High elongation, not easy to break.

Mainly used for safety warning, construction warning, regional isolation etc.

Following data is provided for reference, users should assure themselves that the performance of the product is sufficient for their application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes.

Properties	Unit	Value	Test Method
Material Type	Polyethylene heated extruded film,		
Total Thickness	μ m	30	PSTC-133 / ASTM D 3652
Tensile Strength	N/25mm	10	PSTC-131 / ASTM D 3759
Elongation	%	200	PSTC-131 / ASTM D 3759
Service Temperature	°C	5 to 60	
Applying Temperature	°C	10 to 40	

Storage:

1. Rolls should be stored, flat on their cut edges in their wrappings to avoid any pressure on the glued surface.
2. Rolls should be stored away from sources of heat for example direct sunlight and also frost, Ideal storage temperature is 23± 2°C, 50% relative humidity

Usage Tips:

The surface that the tape is to be applied to must be clean and free from dust and grease.

Others:

Tolerance: Thickness: ±10 μ m; Width: ±1mm; Length: Cut Roll: ±0.3m

Remarks:

Individual rolls will vary slightly from above data, The user should determine whether the product
There is no Warranty of fitness for a particular purpose.