

TECHNICAL DATA SHEET

Product:	Silver Industrial Cloth Duct Tape
Variants:	50mm / 75mm / 100mm width
Product Codes:	BR4004000 / BR4004001/ BR4004002

Product Description:

The tape uses polyethylene and gauze fibre thermal composite as the base material. Then coated with high viscosity synthetic rubber, with strong peeling force, tensile resistance, grease resistance.

Following data is provided for reference, users should assure themselves that the performance of the product is sufficient for their application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes.

Properties	Unit	Value	Test Method
Total Thickness	μ m	160	PSTC-133 / ASTM D 3652
Adhesion to Steel	N/25mm	15	PSTC-101 / ASTM D 3330
Initial Tack	#	8	GB/T 7125-2014
Tensile Strength	N/25mm	65	PSTC-131 / ASTM D 3759
Elongation	%	10	PSTC-131 / ASTM D 3759
Service Temperature	°C	-5 to 60	
Applying Temperature	°C	10 to 40	

Storage:

- Rolls should be stored, flat on their cut edges in their wrappings to avoid any pressure on the glued surface.
- Rolls should be stored away from sources of heat for example direct sunlight and also frost, Ideal storage temperature is 23± 2°C, 50% relative humidity

Usage Tips:

The surface that the tape is to be applied to must be clean and free from dust and grease.

Others:

Tolerance: Thickness: ±10 μ m; Width: ±1mm; Length: Cut Roll: ±0.3m

Remarks:

Individual rolls will vary slightly from above data, The user should determine whether the product There is no Warranty of fitness for a particular purpose.