

WD-40 SPECIALIST® DRY PTFE

DATA
SHEET



PRODUCT OVERVIEW

WD-40® Specialist® Dry PTFE Lubricant contains PTFE which provides enhanced lubrication, leaving a white dry film that won't attract dirt, dust or oil. It's quick drying and great as a mould release agent. This product can be used on **metals, plastic and glass**.



NARROW SPRAY



WIDE SPRAY

FEATURES & BENEFITS

- Dual action Smart Straw® applicator for wide area and precision spray applications
- Ideal to be used on metals, plastic and glass
- Enhanced lubrication and protection
- Produces a white dry film that resists dirt, dust and oil Reduces friction and wear
- Advanced formulation works as an effective mould release agent
- Excellent resistance to high temperature ranging from -45°C to +260°C

RECOMMENDED FOR:

Blades & Drill bits, Power Tools & Equipment, Door & Window Tracks, Locks & Catches, Conveyors, Rollers, Chains & Cables, Hinges, Thermoplastics and Metal Extrusions.

DIRECTIONS FOR USE

Shake can well. Apply by spraying directly on surface to be lubricated and protected. Dries in seconds.

TECHNICAL DATA

Appearance	Slightly cloudy, deep yellow liquid
Odour	Pleasant lemon smell
SG	0.71 - 0.74
Discharge Rate	0.61 - 1.2 g/s
Solubility	Not miscible with water
NSF Category	H2
Flammability	Classed as extremely flammable
Lubrication	Scar depth 0.43mm (ASTM D4172)
Corrosion Protection	40% at 24hr (ASTM B-117)
Extreme Pressure Lubrication	2310lb (ASTM 3233)

